



- NOTE:
- 1.MATERIAL:
 - 1.1 INSULATOR: HIGH TEMPERATURE PLASTIC
 - 1.2 CONTACT: BRONZE
 - 1.3 SHELL: BRASS & K7 & SPCC
 - 2.ELECTRICAL CHARACTERISTICS;
 - 2.1 CONTACT RESISTANCE: 30mΩ MAXIMUM
 - 2.2 CONTACT CURRENT RATING: 1.5A
 - 2.3 DIELECTRIC WITHSTANDING VOLTAGE: 100 V AC R.M.S.
 - 2.4 INSULATION RESISTANCE 100 MEGOHMS MIN
 - 2.5 OPERATING TEMPERATURE: -40°C ~ 85°C
 - 3 MECHANICAL CHARACTERISTICS:
 - 3.1 MATING FORCE: 3.57kgf MAX
 - 3.2 UNMATED FORCE: 0.82kgf MIN AFTER TEST
 - 3.3 DURABILITY MANDATORY: 5,000 CYCLES
 - 4.PLATING
 - 4.1 TERMINAL:
 - 50u" MIN NICKEL ALL OVER
 - 80u" MIN Tin ON SOLDER AREA
 - (1~30)u" Au ON CONTACT AREA
 - 4.2 SHELL: 100u" MIN. NICKEL ALL OVER

PCB EDGE
RECOMMENDED PCB LAYOUT
TOLERANCE: ±0.05mm

设计:	Arvin: 2016.03.08	范围 Range	公差 Tolerance
审核:	Arvin:	X.X ±	X.X ±0.30
校对:	Ru yi:	X.XX ±	X.XX ±0.20
比例:	视角关系:	X.XXX ±	X.XXX ±0.10
版次:	图框大小: A4	Angle ±	Angle ±5°

东莞市恒祺电子科技有限公司

名称: USB插座 料号:
 型号: USB3.0 A/F短体板上6.0MM-SMT直边
 共 张 , 第 张 备注: